

H 8000 TE

powered by **HONDA GX390**

Model H8000TE Compact






1. General Details

Frequency	50 Hz	
Voltage	400/230 V	
Max Power	7,5	KVA
Continuous power	6,8	KVA
Power factor cos ϕ	0,8	
Max Power	6,0	KWe
Continuous power	5,4	KWe

2. Petrol driven engine

Make and model	HONDA	GX390
rpm	3000	
Max power at 3600 rpm	13	HP
Cooling system	Air	
Cylinders	1	
Displacement (cm ³)	389	

3. Alternator						
Make and model	LINZ	E1S10M H				
Max power	8,7	KVA				
Continuous power	7,9	KVA				
4. Starting system						
Electric						
5. Standard Equipment						
<ul style="list-style-type: none"> ✓ Protection Frame ✓ Vibration dampers ✓ Low oil level protection ✓ Exhaust gas silencer ✓ Air filter ✓ Fuel tank ✓ Output sockets with protection ✓ Electric panel model QM 301 						
6. Electric Panels						
QM 301 STANDARD			ACP 0411 available for genset with electronic starting system			
 <ul style="list-style-type: none"> ✓ Three-phase 16A socket 5P ✓ Single-phase 16A socket 3P ✓ Voltmeter ✓ Circuit breaker 			 <ul style="list-style-type: none"> ✓ Control unit ✓ Frequency and voltage indicators ✓ Generating set/mains supply contractors ✓ Automatic battery charger 			
7. Logistic Information						
	Model	Fuel tank (litres)	Weight (Kgs)	Dimensions (cm)		
				L	W	H
	H8000TE compact	6,5	85	78	52	56
8. Fuel consumption						
litres/hour at 75% load		1,9	approx			
9. Marking						
Label showing the general data of the genset (voltage, power, frequency). engine model with serial number, alternator model.						
TECNOGEN LOGO						
10. Operating manuals						
English. Other languages available on request.						