

H 8000 E

powered by **HONDA GX390**

Model H8000E Compact






1. General Details

Frequency	50 Hz	
Voltage	230 V	
Max Power	7,2	KVA
Continuous power	6,5	KVA
Power factor cos ϕ	0,8	
Max Power	5,8	KWe
Continuous power	5,2	KWe

2. Petrol driven engine

Make and model	HONDA	GX390
rpm	3000	
Max power at 3600 rpm	13	HP
Cooling system	Air	
Cylinders	1	
Displacement (cm ³)	389	

3. Alternator						
Make and model	MECCALTE	S20W-95/A				
Max power	7,5	KVA				
Continuous power	6,8	KVA				
4. Starting system						
Electric						
5. Standard Equipment						
<ul style="list-style-type: none"> ✓ Protection Frame ✓ Vibration dampers ✓ Low oil level protection ✓ Exhaust gas silencer 		<ul style="list-style-type: none"> ✓ Air filter ✓ Fuel tank ✓ Output sockets with protection ✓ Electric panel model QM 116 				
6. Electric Panels						
QM 116 STANDARD				ACP 0411 available for genset with electronic starting system		
 <ul style="list-style-type: none"> ✓ 32A Single-phase socket 3P ✓ 16A Single-phase Schuko 3P socket ✓ Thermal shut off 		 <ul style="list-style-type: none"> ✓ Control unit ✓ Frequency and voltage indicators ✓ Generating set/mains supply contractors ✓ Automatic battery charger 				
7. Logistic Information						
	Model	Fuel tank (litres)	Weight (Kgs)	Dimensions (cm)		
				L	W	H
	H8000E compact	6,5	80	78	52	56
8. Fuel consumption						
litres/hour at 75% load		1,9	approx			
9. Marking						
Label showing the general data of the genset (voltage, power, frequency). engine model with serial number, alternator model.						
TECNOGEN LOGO						
10. Operating manuals						
English. Other languages available on request.						